

QSV 205-530 7.5-20hp

Set to meet your specific vacuum demands and tackle your daily challenges, we offer you the variable speed QSV vacuum. Immediately ready to supply high quality vacuum, this powerful solution provides you with the exceptional reliability and efficiency needed for your rough vacuum 6 applications. 4 Air Logic 3 Controller 1) with 7" HMI Touchscreen Premium Efficiency 2 Innovative Oil-Injected 4 Sound Insulating Canopy IE3 motor Screw Airend Modulating Inlet Check Service-Friendly 3 Cyclonic Oil Valve **Oil Separator** Separation <3ppm Design Variable Speed Drive with **Oil Carryover Energy-Saving Setpoint**

Control Technology

QSV 205-530 7.5-20 HP

The QSV Is Best For:

- & Plastic Thermoforming
- Glass Molding
- 🧭 Holding, Lifting, Moving
- & Printing, Envelopes, Other Paper Processes
- Solution Food Packaging/Preservation
- & General Packaging and Canning
- 🛇 Lab, Pharmaceutical, and Medical Vacuum

- Solution Those looking for a premium variable speed rotary screw vacuum option
- \bigotimes Customers with energy efficiency in mind
- Facilities requiring low oil carryover vacuum pumps
- Rough vacuum applications operating at 18-29.9"HgV

Air Logic 3 Controller with 7" HMI Touchscreen

- \cdot Configurable Home Screen Interface
- \cdot 4 Modes Pre-Set at Factory
 - · Medium PI Conrol
 - · Slow PI Control
 - \cdot Forced to Max Speed
 - · Fixed Speed Control
- \cdot Customize Your Own Pump Modes!



QSV 205-530 TECHNICAL DATA



· Plot Any Parameter!

• View Trends of Pump Metrics Over a Customizable Time Period Including Inlet Pressure, Motor Speed, Power Consumption, Oil Temperature, and more.

· Plot Multiple Metrics at Once

· Many Fieldbus Protocols Available Without Gateway!



	Vacuum Pressure		Maximum Displacement		Installed Motor		Max Noise	Weight		Inlet	Outlet
Model No.	Minimum	Maximum					Level	Standard		Size	Size
	HgV	HgV	m³/h	cfm	kW	HP	dB(A)	kg	lb	NPT	NPT
QSV-205	18	29.9	483	284	5.6	7.5	65	500	1102	3″	2.5″
QSV-345	18	29.9	607	357	7.5	10	68	500	1102	3″	2.5″
QSV-430	18	29.9	783	461	11.2	15	73	510	1124	3″	2.5″
QSV-530	18	29.9	877	516	14.9	20	76	520	1146	3″	2.5″

	Standard						
Model	А	В	С				
No.	Length (mm/in)	Width (mm/in)	Height (mm/in)				
QSV-205	1270/50	940/37	1092/43				
QSV-345	1270/50	940/37	1092/43				
QSV-430	1270/50	940/37	1092/43				
QSV-530	1270/50	940/37	1092/43				

WARRANTY INFORMATION

ROYAL BLUE	10 Year Factory Warranty
ROYAL BLUE WARRANTY	Vacuum Pump Package - One year from date of start-up or 18 months from date of shipment from the factory, whichever occurs first.
	Airend - Ten years from date of startup.
YEARS	Air and Fluid Heat Exchangers - 5 years from date of start-up.
WORLD'S BEST	Drive Motors - Five years from date of start-up.
	Drive Coupling Elements - Five years from date of start-up.
	Variable Speed Drives - Five years from date of start-up.
	Oil Separator Tanks - Five years from date of start-up.